A Quick Introduction to C++

Tom Anderson

> "If programming in Pascal is like being put in a straightjacket, then programming in C is like playing with knives, and programming in C++ is like juggling chainsaws."
>
> Anonymous.

1 Introduction

This note introduces some simple C++ concepts and outlines a subset of C++ that is easier to learn and use than the full language. Although we originally wrote this note for explaining the C++ used in the Nachos project, I believe it is useful to anyone learning C++. I assume that you are already somewhat familiar with C concepts like procedures, for loops, and pointers; these are pretty easy to pick up from reading Kernighan and Ritchie's "The C Programming Language."

I should admit up front that I am quite opinionated about C++, if that isn't obvious already. I know several C++ purists (an oxymoron perhaps?) who violently disagree with some of the prescriptions contained here; most of the objections are of the form, "How could you have possibly left out feature X?" However, I've found from teaching C++ to nearly 1000 undergrads over the past several years that the subset of C++ described here is pretty easy to learn, taking only a day or so for most students to get started.

The basic premise of this note is that while object-oriented programming is a useful way to simplify programs, C++ is a wildly over-complicated language, with a host of features that only very, very rarely find a legitimate use. It's not too far off the mark to say that C++ includes every programming language feature ever imagined, and more. The natural tendency when faced with a new language feature is to try to use it, but in C++ this approach leads to disaster.

Thus, we need to carefully distinguish between (i) those concepts that are fundamental (e.g., classes, member functions, constructors) – ones that everyone should know and use, (ii) those that are sometimes but rarely useful (e.g., single inheritance, templates) – ones that beginner programmers should be able to recognize (in case they run across them) but avoid using in their own programs, at least for a while, and (iii) those that are just a bad idea and should be avoided like the plague (e.g., multiple inheritance, exceptions, overloading, references, etc).

Of course, all the items in this last category have their proponents, and I will admit that, like the hated goto, it is possible to construct cases when the program would be simpler

This article is based on an earlier version written by Wayne Christopher.

using a goto or multiple inheritance. However, it is my belief that most programmers will never encounter such cases, and even if you do, you will be much more likely to misuse the feature than properly apply it. For example, I seriously doubt an undergraduate would need any of the features listed under (iii) for any course project (at least at Berkeley this is true). And if you find yourself wanting to use a feature like multiple inheritance, then, my advice is to fully implement your program both with and without the feature, and choose whichever is simpler. Sure, this takes more effort, but pretty soon you'll know from experience when a feature is useful and when it isn't, and you'll be able to skip the dual implementation.

A really good way to learn a language is to read clear programs in that language. I have tried to make the Nachos code as readable as possible; it is written in the subset of C++ described in this note. It is a good idea to look over the first assignment as you read this introduction. Of course, your TA's will answer any questions you may have.

You should not need a book on C++ to do the Nachos assignments, but if you are curious, there is a large selection of C++ books at Cody's and other technical bookstores. (My wife quips that C++ was invented to make researchers at Bell Labs rich from writing "How to Program in C++" books.) Most new software development these days is being done in C++, so it is a pretty good bet you'll run across it in the future. I use Stroustrup's "The C++ Programming Language" as a reference manual, although other books may be more readable. I would also recommend Scott Meyer's "Effective C++" for people just beginning to learn the language, and Coplien's "Advanced C++" once you've been programming in C++ for a couple years and are familiar with the language basics. Also, C++ is continually evolving, so be careful to buy books that describe the latest version (currently 3.0, I think!).

2 C in C++

To a large extent, C++ is a superset of C, and most carefully written ANSI C will compile as C++. There are a few major caveats though:

1. All functions must be declared before they are used, rather than defaulting to type `int`.

2. All function declarations and definition headers must use new-style declarations, e.g.,

   ```
   extern int foo(int a, char* b);
   ```

   The form `extern int foo();` means that `foo` takes *no* arguments, rather than arguments of an unspecified type and number. In fact, some advise using a C++ compiler even on normal C code, because it will catch errors like misused functions that a normal C compiler will let slide.

3. If you need to link C object files together with C++, when you declare the C functions for the C++ files, they must be done like this:

```
extern "C" int foo(int a, char* b);
```

Otherwise the C++ compiler will alter the name in a strange manner.

4. There are a number of new keywords, which you may not use as identifiers — some common ones are `new`, `delete`, `const`, and `class`.

3 Basic Concepts

Before giving examples of C++ features, I will first go over some of the basic concepts of object-oriented languages. If this discussion at first seems a bit obscure, it will become clearer when we get to some examples.

1. **Classes and objects**. A class is similar to a C *structure*, except that the definition of the data structure, *and* all of the functions that operate on the data structure are grouped together in one place. An *object* is an instance of a class (an instance of the data structure); objects share the same functions with other objects of the same class, but each object (each instance) has its own copy of the data structure. A class thus defines two aspects of the objects: the *data* they contain, and the *behavior* they have.

2. **Member functions**. These are functions which are considered part of the object and are declared in the class definition. They are often referred to as *methods* of the class. In addition to member functions, a class's behavior is also defined by:

   (a) What to do when you create a new object (the **constructor** for that object) – in other words, initialize the object's data.

   (b) What to do when you delete an object (the **destructor** for that object).

3. **Private vs. public members**. A public member of a class is one that can be read or written by anybody, in the case of a data member, or called by anybody, in the case of a member function. A private member can only be read, written, or called by a member function of that class.

Classes are used for two main reasons: (1) it makes it much easier to organize your programs if you can group together data with the functions that manipulate that data, and (2) the use of private members makes it possible to do *information hiding*, so that you can be more confident about the way information flows in your programs.

3.1 Classes

C++ classes are similar to C structures in many ways. In fact, a C++ struct is really a class that has only public data members. In the following explanation of how classes work, we will use a stack class as an example.

1. **Member functions.** Here is a (partial) example of a class with a member function and some data members:

```
class Stack {
  public:
    void Push(int value); // Push an integer, checking for overflow.
    int top;          // Index of the top of the stack.
    int stack[10];    // The elements of the stack.
};

void
Stack::Push(int value) {
    ASSERT(top < 10); // stack should never overflow
    stack[top++] = value;
}
```

This class has two data members, `top` and `stack`, and one member function, `Push`. The notation *class*::*function* denotes the *function* member of the class *class*. (In the style we use, most function names are capitalized.) The function is defined beneath it.

As an aside, note that we use a call to `ASSERT` to check that the stack hasn't overflowed; ASSERT drops into the debugger if the condition is false. It is an extremely good idea for you to use ASSERT statements liberally throughout your code to document assumptions made by your implementation. Better to catch errors automatically via ASSERTs than to let them go by and have your program overwrite random locations.

In actual usage, the definition of `class Stack` would typically go in the file `stack.h` and the definitions of the member functions, like `Stack::Push`, would go in the file `stack.cc`.

If we have a pointer to a `Stack` object called `s`, we can access the `top` element as `s->top`, just as in C. However, in C++ we can also call the member function using the following syntax:

```
s->Push(17);
```

Of course, as in C, `s` must point to a valid `Stack` object.

Inside a member function, one may refer to the members of the class by their names alone. In other words, the class definition creates a scope that includes the member (function and data) definitions.

Note that if you are inside a member function, you can get a pointer to the object you were called on by using the variable `this`. If you want to call another member function on the same object, you do not need to use the `this` pointer, however. Let's extend the Stack example to illustrate this by adding a `Full()` function.

```
class Stack {
  public:
    void Push(int value); // Push an integer, checking for overflow.
    bool Full();       // Returns TRUE if the stack is full, FALSE otherwise.
    int top;          // Index of the lowest unused position.
    int stack[10];    // A pointer to an array that holds the contents.
};
```

```
bool
Stack::Full() {
    return (top == 10);
}
```

Now we can rewrite `Push` this way:

```
void
Stack::Push(int value) {
    ASSERT(!Full());
    stack[top++] = value;
}
```

We could have also written the ASSERT:

```
    ASSERT(!(this->Full());
```

but in a member function, the `this->` is implicit.

The purpose of member functions is to encapsulate the functionality of a type of object along with the data that the object contains. A member function does not take up space in an object of the class.

2. **Private members.** One can declare some members of a class to be *private*, which are hidden to all but the member functions of that class, and some to be *public*, which are visible and accessible to everybody. Both data and function members can be either public or private.

   In our stack example, note that once we have the `Full()` function, we really don't need to look at the `top` or `stack` members outside of the class – in fact, we'd rather that users of the Stack abstraction *not* know about its internal implementation, in case we change it. Thus we can rewrite the class as follows:

```
class Stack {
  public:
    void Push(int value); // Push an integer, checking for overflow.
    bool Full();       // Returns TRUE if the stack is full, FALSE otherwise.
  private:
    int top;          // Index of the top of the stack.
    int stack[10];    // The elements of the stack.
};
```

Before, given a pointer to a Stack object, say s, any part of the program could access s->top, in potentially bad ways. Now, since the top member is private, only a member function, such as Full(), can access it. If any other part of the program attempts to use s->top the compiler will report an error.

You can have alternating public: and private: sections in a class. Before you specify either of these, class members are private, thus the above example could have been written:

```
class Stack {
    int top;          // Index of the top of the stack.
    int stack[10];    // The elements of the stack.
  public:
    void Push(int value); // Push an integer, checking for overflow.
    bool Full();       // Returns TRUE if the stack is full, FALSE otherwise.
};
```

Which form you prefer is a matter of style, but it's usually best to be explicit, so that it is obvious what is intended. In Nachos, we make everything explicit.

What is not a matter of style: **all data members of a class should be private.** All operations on data should be via that class' member functions. Keeping data private adds to the modularity of the system, since you can redefine how the data members are stored without changing how you access them.

3. **Constructors and the operator new.** In C, in order to create a new object of type Stack, one might write:

```
    struct Stack *s = (struct Stack *) malloc(sizeof (struct Stack));
    InitStack(s, 17);
```

The InitStack() function might take the second argument as the size of the stack to create, and use malloc() again to get an array of 17 integers.

The way this is done in C++ is as follows:

```
    Stack *s = new Stack(17);
```

The new function takes the place of malloc(). To specify how the object should be initialized, one declares a *constructor* function as a member of the class, with the name of the function being the same as the class name:

```
class Stack {
  public:
    Stack(int sz);    // Constructor:  initialize variables, allocate space.
    void Push(int value); // Push an integer, checking for overflow.
    bool Full();       // Returns TRUE if the stack is full, FALSE otherwise.
  private:
    int size;          // The maximum capacity of the stack.
    int top;           // Index of the lowest unused position.
    int* stack;        // A pointer to an array that holds the contents.
};

Stack::Stack(int sz) {
    size = sz;
    top = 0;
    stack = new int[size];   // Let's get an array of integers.
}
```

There are a few things going on here, so we will describe them one at a time.

The `new` operator automatically creates (i.e. allocates) the object and then calls the constructor function for the new object. This same sequence happens even if, for instance, you declare an object as an automatic variable inside a function or block – the compiler allocates space for the object on the stack, and calls the constructor function on it.

In this example, we create two stacks of different sizes, one by declaring it as an automatic variable, and one by using `new`.

```
void
test() {
    Stack s1(17);
    Stack* s2 = new Stack(23);
}
```

Note there are two ways of providing arguments to constructors: with `new`, you put the argument list after the class name, and with automatic or global variables, you put them after the variable name.

It is crucial that you **always** define a constructor for every class you define, and that the constructor initialize **every** data member of the class. If you don't define your own constructor, the compiler will automatically define one for you, and believe me, it won't do what you want ("the unhelpful compiler"). The data members will be initialized to random, unrepeatable values, and while your program may work anyway, it might not the next time you recompile (or vice versa!).

As with normal C variables, variables declared inside a function are deallocated automatically when the function returns; for example, the `s1` object is deallocated when `test` returns. Data allocated with `new` (such as `s2`) is stored on the heap, however, and remains after the function returns; heap data must be explicitly disposed of using `delete`, described below.

The `new` operator can also be used to allocate arrays, illustrated above in allocating an array of `int`s, of dimension `size`:

```
    stack = new int[size];
```

Note that you can use `new` and `delete` (described below) with built-in types like `int` and `char` as well as with class objects like `Stack`.

4. **Destructors and the operator delete.** Just as `new` is the replacement for `malloc()`, the replacement for `free()` is `delete`. To get rid of the `Stack` object we allocated above with `new`, one can do:

```
    delete s2;
```

This will deallocate the object, but first it will call the *destructor* for the `Stack` class, if there is one. This destructor is a member function of `Stack` called `~Stack()`:

```
class Stack {
  public:
    Stack(int sz);    // Constructor:  initialize variables, allocate space.
    ~Stack();         // Destructor:   deallocate space allocated above.
    void Push(int value); // Push an integer, checking for overflow.
    bool Full();      // Returns TRUE if the stack is full, FALSE otherwise.
  private:
    int size;         // The maximum capacity of the stack.
    int top;          // Index of the lowest unused position.
    int* stack;       // A pointer to an array that holds the contents.
};

Stack::~Stack() {
    delete [] stack;  // delete an array of integers
}
```

The destructor has the job of deallocating the data the constructor allocated. Many classes won't need destructors, and some will use them to close files and otherwise clean up after themselves.

The destructor for an object is called when the object is deallocated. If the object was created with `new`, then you must call `delete` on the object, or else the object will continue to occupy space until the program is over – this is called "a memory leak." Memory leaks are bad things – although virtual memory is supposed to be unlimited, you can in fact run out of it – and so you should be careful to **always** delete what you allocate. Of course, it is even worse to call `delete` too early – `delete` calls the destructor and puts the space back on the heap for later re-use. If you are still using the object, you will get random and non-repeatable results that will be very difficult to debug. In my experience, using data that has already been deleted is major source of hard-to-locate bugs in student (and professional) programs, so hey, be careful out there!

If the object is an automatic, allocated on the execution stack of a function, the destructor will be called and the space deallocated when the function returns; in the `test()` example above, `s1` will be deallocated when `test()` returns, without you having to do anything.

In Nachos, we always explicitly allocate and deallocate objects with `new` and `delete`, to make it clear when the constructor and destructor is being called. For example, if an object contains another object as a member variable, we use `new` to explicitly allocated and initialize the member variable, instead of implicitly allocating it as part of the containing object. C++ has strange, non-intuitive rules for the order in which the constructors and destructors are called when you implicitly allocate and deallocate objects. In practice, although simpler, explicit allocation is slightly slower and it makes it more likely that you will forget to deallocate an object (a bad thing!), and so some would disagree with this approach.

When you deallocate an array, you have to tell the compiler that you are deallocating an array, as opposed to a single element in the array. Hence to delete the array of integers in `Stack::~Stack`:

```
delete [] stack;
```

3.2 Other Basic C++ Features

Here are a few other C++ features that are useful to know.

1. When you define a `class Stack`, the name `Stack` becomes usable as a type name as if created with `typedef`. The same is true for `enum`s.

2. You can define functions inside of a `class` definition, whereupon they become *inline functions*, which are expanded in the body of the function where they are used. The rule of thumb to follow is to only consider inlining one-line functions, and even then do so rarely.

   As an example, we could make the `Full` routine an inline.